



DECLARATION OF PERFORMANCE NO. FS-SP1809-01

| | |
|--|--|
| Unique identification code of the product-type | LINEAR 310ml Art. No. 100898 LINEAR 600ml Art. No. 100900 |
| Intended use: | Sealant for façade for interior application (F-INT) |
| Manufacturer: | FireSeal AB Esbogatan 14, SE-164 74 Kista SWEDEN |
| System of AVCP: | SYSTEM 4 |
| European Assessment Document EAD): | Not relevant |
| Technical Assessment Body (TAB) | Not relevant (System 4) |
| Harmonised EN Standard | EN 15651-1:2012 |

Declared performances:


| Essential Characteristics | Declared Performance | Harmonised Technical Specification |
|--|-----------------------------------|------------------------------------|
| Reaction to Fire | Class F | EN 13501-1:2007+A1:2009 |
| Release of chemicals dangerous to the environment and health | NPD/see product safety data sheet | EN 15651-1:2012 |
| Water tightness and air tightness | | |
| • Resistance to flow (EN ISO 7390) | ≤ 5 mm | |
| • Loss of volume (EN ISO 10563) | ≤ 45 % | |
| • Tensile properties at break (EN ISO 8339) | ≥ 25% | |
| Durability | Pass | |
| Conditioning: Method A / Tested on aluminum, without primer | | |

NPD = No Performance Determined

| | |
|---|---|
| Link to an electronic copy of the performance declaration and installation instructions | http://fireseal.se |
|---|---|

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above:

Signed for and on the behalf of the manufacturer by:
Kista Sweden, 2018.10.01


Anders Wigant
Product Manager