

## Wood screw WAF with a large head, A4

### Area of usage

ESSVE Wood screw WAF A4 with 1 fibre cut in the tip and TX drive intended for most installation work in wood, chipboard, plywood etc. outdoor in demanding conditions and environment.

### Description

Wood screw WAF A4 is produced in stainless, acid proof steel corrosion class C5, for use in demanding environment like polluted areas and areas with high saline level such as close to coastal areas. The screw has a large head diameter which produces a very high clamping force during installation. The head also has a very low inset height, which can be an advantage during installation. It is equip-

ped with 1 fibre cut in the tip, which gives the screw a low drive in torque and minimizes the risk of splintering. Another benefit is the elimination of the need for predrilling. On screws longer than 70mm, there is an additional fibre cut milling thread directly above the normal thread, this is to facilitate installation of longer and thicker screws. The underside of the screw head is designed so that it fits properly when installed in beams and timber brackets. ESSVE Wood screw WAF conforms to the CE requirement according to EN 14592. The screw is fitted with Tx-bit drive.



### Assembly

Recommended rpm: 400-1200/min.

Material	Stainless Steel AISI 316
Surface treatment	Wax
Corrosivity Class	C5

### ESSBOX

Item numb.:	Dimension dk x L mm	D mm	B mm	Bits numb.:	ESSBOX numb.:	Pce/PC	PC/Outherbox
113306	6,0X70	14	50	TX30	203	50	8
113310	6,0X90	14	50	TX30	203	50	8
113314	6,0X120	14	70	TX30	204	50	6
113325	8,0X40	22	40	TX40	203	50	8
113330	8,0X70	22	50	TX40	204	50	6
113334	8,0X90	22	50	TX40	206	50	4
113338	8,0X120	22	70	TX40	204	25	6
113340	8,0X150	22	80	TX40	206	25	4
113376	10,0X40	26	40	TX40	204	50	6
113382	10,0X70	26	50	TX40	206	50	4
113357	10,0X90	26	70	TX40	204	25	6
113360	10,0X120	26	70	TX40	206	25	4
113363	10,0X150	26	90	TX40	206	25	4